

UNDERWATER TILE REPAIR MORTAR

- Replaces broken tile underwater
- Sets tile in minutes
- Easy to use

PRODUCT DESCRIPTION

This unique product allows you to replace broken tile underwater. No need to drain fountains, pools or spas. Easy to use – sets tile in minutes.

USES — TILE TYPES

Replacing ceramic, mosaic, porcelain and quarry tiles, cement tile, precast terrazzo and natural stone while underwater.

AREAS OF USE

- Concrete or masonry

LIMITATIONS

- This product can be harmful to aquatic fish and plants during installation.

SURFACE PREPARATION

Surface must be structurally sound and free of all loose tile and debris, existing setting material or any other foreign matter. When necessary, use a hammer and chisel to remove broken tile and mortar so area is clean.

MIXING

Pour approximately 4 oz. (118.3 ml) clean water into a mixing container, then add the 1 lb. (.45 kg) bag of mortar. Mix vigorously for 2 - 3 minutes. The mixture is ready for immediate application; no waiting required. Re-stir occasionally to ensure a creamy, smooth consistency but do not add more water. If the mortar begins to harden, discard and mix fresh material.

APPLICATION

Apply mortar to the back of the replacement tile with the flat side of a trowel held at a 35° - 40° angle. This forces the mortar into any depressions between ridges or grooves for maximum coverage and adhesion. Then apply a generous amount of mortar to the back of the tile and comb through the mortar with the notched side of the trowel to ensure uniform coverage. The type and size of the tile will determine the size of the notched trowel. The tile can then be taken underwater for installation. Press the coated tile firmly onto the prepared area making sure the tile is set flush with adjacent tile. The excess mortar should squeeze up out of the surrounding joints. Remove this excess but leave enough to serve as the grout. The tile can be adjusted for several minutes after placement.

CURING

Do not disturb tile for a minimum of 24 hours.

COVERAGE

1 lb. (.45 kg) package will cover approximately 2 sq. ft (.186 m²).

CLEAN-UP

Clean with water before material dries.

STORAGE

Store in a cool dry area.

SAFETY

Contains Portland cement. Wear rubber gloves and eye protection. Avoid eye contact or prolonged contact with skin. Wash thoroughly after handling. If eye contact occurs, flush with water for 15 minutes. Consult physician immediately. This product contains Free Silica. Do not breathe dust; wear NIOSH approved respirator.

ORDERING INFORMATION

ITEM CODE	SIZE	COLOR	PACKAGE
UTR1	1 lb. (.45 kg)	White	Tub



CUSTOM[®]
BUILDING PRODUCTS