

CUSTOMFLEX™ ULTRA-STRENGTH THIN-SET ADDITIVE

- Mix with MasterBlend™ Thin-Set Mortar for a high strength, flexible system
- Substantially increases bond strength
- Adds flexibility – can bridge cracks up to 1/16" (1.6 mm) wide
- Excellent for setting dense tile or stone
- For bonding over plywood, vinyl or smooth concrete surfaces

PRODUCT DESCRIPTION

CustomFlex™ Ultra-Strength Thin-Set Additive is an advanced acrylic latex additive that substantially increases bond strength and flexibility when combined with MasterBlend™ or PremiumPlus® Standard Thin-Set Mortars. Excellent for use over difficult to bond to surfaces such as plywood and vinyl and when setting hard-to-bond vitreous or non-porous tile and stone. Adds flexibility to unmodified thin-sets, producing a mortar that can bridge minor cracks up to 1/16" (1.6 mm) wide and withstand minor deflection.

USES

- Add to PremiumPlus or MasterBlend Thin-Set Mortars
- To meet ANSI A118.4 and A118.11 installation requirements
- When setting impervious porcelain tile, glass mosaics or when higher bond strength is desired
- Interior and exterior floors, walls, countertops
- Areas subject to freeze-thaw cycles
- Exterior grade plywood (interior residential and light commercial dry areas)
- Existing ceramic tile
- Sheet vinyl flooring, VCT
- Plastic laminates
- Cutback adhesive

FOR USE AS AN ADMIX WITH CUSTOM STANDARD THIN-SET MORTARS

Refer to individual product data sheets for detailed installation instructions.

COVERAGE

Refer to individual Custom® Standard thin-set mortars.

CLEAN-UP

Clean with soap and water before material dries. Cured material is difficult to clean from surfaces.

STORAGE

Keep from freezing. Close container after each use.

SAFETY

Do not take internally. Avoid eye and skin contact. If eye contact occurs, immediately flush with water for 15 minutes and consult a physician. If skin contact occurs, wash immediately with soap and water. Dried material becomes extremely difficult to remove.

ORDERING INFORMATION

ITEM CODE	SIZE	PACKAGE
CF2P	2 gallon (7.57 L)	Pail
CF5	5 gallon (18.93 L)	Pail



CUSTOM®
BUILDING PRODUCTS