

TILELAB®

STONE ENHANCER & SEALER

- Protects and color enhances marble, stone and grout
- Penetrating sealer resists dirt and stains
- Enriches the color and texture of stone

PRODUCT DESCRIPTION

Color enhancer and penetrating sealer for all types of porous natural stone and grout. Rejuvenates the color and appearance of worn, faded stone, tumbled marble and other rustic-look stones. Can also be used to darken the color of grout giving it a "wet look." Provides long-lasting protection against oil, grease and stains. Its water-based, low odor formula can be used indoors or outdoors. Improved formula.

USES

As a sealer and color enhancer for all stone surfaces, clay pavers and grout. Excellent for tumbled marble and other rustic look stones. This product may not be totally effective as a color enhancer on some polished stones. For interior and exterior use.

SURFACE PREPARATION

Surface should be dry, clean and free of waxes, sealers or finishes. TileLab® Heavy-Duty Cleaner & Stripper will clean the surface or strip wax and acrylic finishes. New installations need to be cured 48 - 72 hours before application. Always test product in hidden area to ensure desired results.

APPLICATION

Apply Stone Enhancer & Sealer liberally using a new mop, lambswool applicator or sponge. Allow to penetrate for 3 - 5 minutes. Buff dry any excess. Immediately apply a second coat following the same procedure. Ensure no residue is left to dry on the surface. Surface of stone should be maintained at a temperature above 50° F or below 100° F until sealer cures. Do not use exterior if inclement weather is expected within 24 hours. Clean off any residue left on the surface with an appropriate TileLab cleaner.

Note: The more porous the stone the deeper the color enhancement.

COVERAGE

On Porous Surfaces:

170 - 340 sq. ft. per gallon (15.7-31.5 sq. m per 3.78 L).

43 - 85 sq. ft. per quart (4.2-8.3 sq. m per 946 ml).

On Polished or Dense Surfaces:

680 - 1020 sq. ft. per gallon (63-94.5 sq. m per 3.78 L).

170 - 255 sq. ft. per quart (16.6-25 sq. m per 946 ml).

CLEAN-UP

Clean tools and hands with soap and water immediately after use.

DRYING TIME

4 - 6 hours.

PACKAGING

1 quart (946 ml) and 1 gallon (3.78 L) bottle.

ITEM CODES

TLSESQT, TLSES1

CAUTION

Keep out of reach of children. May be harmful if swallowed. Do not induce vomiting. Give plenty of water and call a physician immediately. If eye contact occurs, flush immediately with plenty of water for 15 minutes. If contact with sensitive skin occurs, wash with soap and water. Call physician if necessary. Do not mix with other solutions. Keep from freezing.



CUSTOM®
BUILDING PRODUCTS